



# Product Guide

|                             | Model name                  | Thickness<br>(mm)<br>(inch)                 | Compressibility | Heat set     |             | Cold set | Sheetfed |      |         |    |           |              | Metal | Image reproductively |     | Paper release | Sticky back  | Comment   |
|-----------------------------|-----------------------------|---|-----------------|--------------|-------------|----------|----------|------|---------|----|-----------|--------------|-------|----------------------|-----|---------------|--|---|
|                             |                             |   |                 | Coated paper | Rough paper |          | Thick    | Thin | Varnish | UV | Perfector | small offset |       | Solid                | Dot |               |  |   |
| Sheetfed                    | <b>FIT 10</b>               | 1.68 / 1.95<br>0.067 / 0.077                | Semi soft       | —            | —           | —        | ○        | ○    | —       | —  | ○         | ○            | ○     | ○                    | ◎   | ◎             | —  | High quality sheetfed.<br>High-end printing.            |
|                             | <b>FS-50</b>                | 1.68 / 1.95<br>0.067 / 0.077                | Semi hard       | —            | —           | —        | ○        | ○    | —       | —  | ○         | ○            | ◎     | ◎                    | ○   | ○             | —  | General sheetfed.<br>Higher color, good smash recovery. |
|                             | <b>FS-70</b>                | 1.68 / 1.95<br>0.067 / 0.077                | Semi hard       | —            | —           | —        | ○        | —    | —       | ○  | —         | —            | ○     | ○                    | —   | ○             | —  | Sheetfed.<br>Hybrid & superior anti-dust pilling.       |
|                             | <b>FS-100</b>               | 1.68 / 1.95<br>0.067 / 0.077                | Semi hard       | —            | —           | —        | ○        | —    | —       | ◎  | —         | —            | ○     | ○                    | ○   | ○             | —  | Sheetfed. Metal decoration.<br>UV only.                 |
|                             | <b>FIT UV</b>               | 1.68 / 1.95<br>0.067 / 0.077                | Semi soft       | —            | —           | —        | ○        | —    | —       | ◎  | —         | —            | ○     | ○                    | ○   | ○             | —  | Sheetfed, Metal decoration.<br>UV only.                 |
| Heatset Web                 | <b>FIT Web</b>              | 1.68 / 1.95<br>0.067 / 0.077                | Semi soft       | ◎            | ◎           | —        | —        | —    | —       | —  | —         | —            | ○     | ◎                    | ○   | —             | Heatset on Rougher Paper.                                      |   |
| Coldset Web<br>(News paper) | <b>FIT News</b>             | 1.68 / 1.95 / 2.10<br>0.067 / 0.077 / 0.082 | Semi soft       | —            | —           | ◎        | —        | —    | —       | —  | —         | —            | ○     | ◎                    | ○   | —             | General newspaper printing.<br>Negative paper feeding.         |   |
| Business Form               | <b>FIT Form</b>             | 0.95 / 1.05<br>0.037 / 0.041                | Semi soft       | —            | —           | —        | —        | —    | —       | —  | —         | —            | ○     | ◎                    | —   | ○             | Business form, Envelope printing.<br>Hybrid, Sticky back type. |   |
| Varnish                     | <b>FIT Coat<br/>(FP-75)</b> | 1.68 / 1.95<br>0.067 / 0.077                | Soft            | —            | —           | —        | —        | —    | ◎       | —  | —         | —            | —     | —                    | —   | ○             | Stripping blanket for coating.                                 |   |
| Under                       | <b>FUJI PAT</b>             | 0.5 / 0.8 / 1.0<br>0.025 / 0.040            | Soft            | —            | —           | —        | —        | —    | —       | —  | —         | —            | —     | —                    | —   | —             | Under packing blanket.   |   |

## Contact



**FUJIKURA RUBBER LTD.** TOC Ariake East Tower 10F, 3-5-7, Ariake, Koto, Tokyo, Japan 135-0063  
**藤倉ゴム工業株式会社** TEL : +81 (3) 3527 8485 FAX : +81 (3) 3527 8520 E mail : info@fujikuragraphics.com

FUJIKURA GRAPHICS obtained ISO 14001 Certification for environmental management system, and ISO 9001 Quality System Certification.

The content described in this catalog is the one as of March, 2012. The specification and the appearance of each product might change without a previous notice for the improvement.

